

United States Patent [19]

Kim et al.

[11] Patent Number:

5,825,569

[45] Date of Patent:

Oct. 20, 1998

[54]	CONSTANT-DENSITY MAGNETIC DISC
	APPARATUS AND MAGNETIC DISC USED
	THEREFOR

[75] Inventors: Jin-Seok Kim; Jae-Deog Joo, both of

Incheon, Rep. of Korea

[73] Assignee: SamSung Electronics Co., Ltd.,

Kyungki-do, Rep. of Korea

[21] Appl. No.: 597,312

[22] Filed: Feb. 6, 1996

[30] Foreign Application Priority Data

 Feb. 8, 1995 [KR]
 Rep. of Korea
 2270/1995

 [51]
 Int. Cl.⁶
 G11B 20/12

 [52]
 U.S. Cl.
 360/51; 360/48

 [58]
 Field of Search
 360/48, 49, 51,

360/

360/77.08

[56] References Cited

U.S. PATENT DOCUMENTS

4,682,253	3 7/1987	Leslie.
4,811,135	35 3/1989	Janz .
4,823,212	2 4/1989	Knowles et al
4,956,727	27 9/1990	Bezinque et al 360/49
4,977,472	72 12/1990	Volz et al
5,121,280	30 6/1992	King .
5,257,149	19 10/1993	Meyer 360/78.14
4,823,212 4,956,727 4,977,472 5,121,280	12 4/1989 27 9/1990 72 12/1990 30 6/1992	Knowles et al Bezinque et al

5,278,703	1/1994	Rub et al.	360/51
5,327,302	7/1994	Khoury et al	360/51 X
5,345,342	9/1994	Abbott et al	360/48
5,544,135	8/1996	Akin, Jr. et al	360/77.08 X
5,587,850	12/1996	Ton-that	360/77.08
5 631 783	5/1997	Park	360/51

Primary Examiner—Aristotelis M. Psitos Assistant Examiner—K. Wong

Attorney, Agent, or Firm-Robert E. Bushnell, Esq.

[7] ABSTRACT

A magnetic disc used in a constant-density magnetic disc driving apparatus includes a wedge identification field following a servo information area that contains a wedge identification for identifying a plurality of data sectors located within a corresponding data information area. A pseudo identification field positioned at a first portion of each data sector represents a time interval required to generate from the wedge identification a pseudo identification that identifies a corresponding one of the data sectors and transfer the pseudo identification to a controller of the magnetic disc driving apparatus. The pseudo identification field includes a data preamble for providing data synchronization for the corresponding data sector. A data field is positioned behind the pseudo identification field, and the data field and pseudo identification field make up a single data sector. Data that is identified by the pseudo identification and synchronized by the data preamble is written in the data field.

13 Claims, 5 Drawing Sheets

